

THE
NORFOLK
COMPANIES
Since 1934

NO PARTICLEBOARD!
Fully-assembled cabinet with
durable, all-wood construction



Honey Finish Hardwood Coronet® Stock Cabinetry

AVAILABLE IN-STOCK FROM OUR WAREHOUSE

Multi-Family Sales - MA: 617-313-5050

NH: 603-577-5450

EXTREME CONSTRUCTION

PROVIDES STRENGTH & DURABILITY

Extreme Cabinets are **ONLY** available in the following door styles:
Oak: Branford, Hampton; **Plantation Hardwood:** Coronet;
Birch: Siena 5-PC/Slab, Tuscany 5-PC/Slab, Vista;
Maple: Berkshire, Calibra II, Caruth, Newbury, Novara,
 Rutledge 5-PC/Slab, and Trevant 5-PC/Slab; **Painted:** Calibra II

1 FRONT FRAME

3/4" thick kiln dried hardwood:
 stiles 1-1/2" wide, mulls 3" wide, rails 1-3/4" wide

2 END PANELS

Nominal 1/2" (12mm) thick, multi-ply Type 1 exterior glue
 hardwood plywood dadoed to receive tops and bottoms.
Optional upgrades available.

3 TOP/BOTTOM PANELS

Nominal 1/2" (12mm) thick multi-ply hardwood plywood

4 HANGING RAILS

Wall cabinets: nominal 3/4" (18mm) thick by 3" high multi-ply hardwood
 plywood running full cabinet width at the top and bottom. Base cabinets:
 3/4" (18mm) thick by 7-1/4" high running full cabinet width at top.

5 BACK PANEL

Nominal 1/4" (6mm) thick hardwood plywood

6 SHELVES

Nominal 1/2" (12mm) thick multi-ply hardwood
 plywood, 10-7/8" deep with banded front edge.
 Shelves are fixed into dadoes in end panels on
 all cabinets.

7 TOE BOARD

Toe kick is 4" high and recessed 4-9/16". 3/4" thick,
 ACQ* pressure treated toe board captured between
 end panels. *Optional upgrades available.*

8 BASE I-BEAM BRACES

Two 1/2" thick (12mm) x 2 7/8" wide plywood
 braces running full-depth front to back of cabinet,
 recessed down 1" from top. All braces are glued
 and stapled at top of cabinet to front frame and hang rail, and dadoed into end panel.

9 DRAWERS

Nominal 5/8" (16mm) thick solid wood front, back, and sides with dovetail construction. Drawer
 bottoms are nominal 1/4" (6mm) multi-ply inserted and stapled into dado in front, back, and sides.

10 DRAWER GUIDES

High-quality epoxy coated steel, extreme grade, side mounted guides, self-adjusting in mounting
 brackets, built-in stop, self-closing, and stay-closed features with a 75lb. rated load capacity.
Optional upgrade available.

11 HINGES

Heavy-duty, high-quality steel, concealed 6-way adjustable hinge with self-closing feature.
Optional upgrade available.



*Toe Board is made of "ACQ" Alkaline Copper
 Quaternary pressure treated lumber meeting AWPA
 Standard C2. The EPA awarded its "Presidential
 Green Chemistry Challenge Award" to Chemical
 Specialties, Inc. the developer of ACQ, an industry
 leader in non-arsenic wood preservatives.



Your Trusted Partner For Multi-Family
 Cabinets & Countertops

thenorfolkcompanies.com

617-313-5050